



Nitrile

## Ergonomically designed with exceptional grip

- **Distinctive black color:** Hides dirt, stains, oils and grease while making light objects more visible
- **Fully textured non-foaming design:** For secure grip in dry and wet conditions
- **Fentanyl- and gastric acid-tested:** For enhanced user protection



### Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment
- Healthcare
- Emergency Medical Services
- Utilities
- Warehousing

### Recommended For

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Use of cleaning tools and robotic equipment
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Blending, compounding solids and liquids
- Raw material sample collection
- Weighing and dispensing of solid and liquid raw materials
- Inspection (picking, checking and marking)
- Standard, moderate risk examination procedures
- Protection from Type I latex allergy in HCW's or patients



# TECHNICAL DATA SHEET

| Product Information    |   |
|------------------------|---|
| External Glove Surface | Fully Textured  |
| Audit Standards        | ISO 13485:2003  |
| Packaging Overview     | 100 gloves per dispenser<br>10 dispensers per case<br>1000 gloves per case<br><br><u>Also available in retail packs</u><br>10 gloves per pack<br>50 packs per carton/case |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.  |
| Country Of Origin      | Malaysia  |
| Product Segmentation   | Robust  |
| Antistatic             | Yes   |

## PHYSICAL PROPERTIES

|   | Typical Values      |                    | Testing Method      |
|---|---------------------|--------------------|---------------------|
| Length (mm/inches)                      | 245 / 9.6           |                    | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 1.5 AQL             |                    | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.12 / 4.7          |                    | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.15 / 6.0          |                    | ASTM D3767,EN 420   |
|   | <b>BEFORE AGING</b> | <b>AFTER AGING</b> |                     |
| Ultimate Tensile Strength (MPa)         | 24                  | 20                 | ASTM D412 & D573    |
| Elongation at Break (%)                 | 600                 | 500                | ASTM D412           |
| Force at break (N)                      | 7                   | 6                  | EN 455-2            |

## ORDERING INFORMATION

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) |
|--------------|--------------|-------------|-------------|-------------|---------------|-----------------|
| Product Code | MK-296-XS    | MK-296-S    | MK-296-M    | MK-296-L    | MK-296-XL     | MK-296-XXL      |

## Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

### Asia Pacific Region

MY +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

### North America Region

Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
T: +52 442 248 1544 / 248 3133

### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

### Russia

Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2022 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

